




eTOP507MFB

The eTOP507MFB is an HMI product specifically designed for applications in food and beverage industry. Product design conforms to the guidelines in DIN EN 1672-2 "Food processing machinery – Safety and hygiene requirements". The stainless steel bezel is safe and resistant to the most critical conditions; the profile allows easy cleaning. Front foil is in polyesther. Gasket is conforming to food standards. The protection degree IP69K allows for high-pressure, high-temperature cleaning. The product can be installed in food areas without any additional protection.

The eTOP507MFB features a high-brightness, contrast-enhanced ruggedized 7" TFT widescreen (16:9) display with LED backlight. The durable projected capacitive touchscreen requires the human touch, eliminating false activations, can be operated with thin gloves.



- High Brightness 7" TFT color display, LED backlight
- 800x480 pixel (WVGA) resolution, 64K colors
- Projected Capacitive Touchscreen (PCT)
- 2 Ethernet ports with switch function
- 2 USB host ports
- SD Card Slot
- Optional plug-in modules
- Slim design. Mounting depth less than 50mm without plugin

Highlights

The eTOP Series 500 HMI products have been designed to run the JMobile software.

- Compatible with JMobileStudio.
- Full vector graphic support. Native support of SVG graphic objects, trasparency and alpha blending.
- Screen object dynamics: control visibility and transparency, move, resize, rotate any object on screen. Change properties of basic and complex objects.
- Multilanguage applications with TrueType fonts. Easily create, install and maintain applications in multiple languages to meet global requirements.
- Data display in numerical, text, bargraph, analog gauges and graphic image formats.
- Rich set of state-of-the-art HMI features: data acquisition and logging, trend presentation, alarm handling, scheduler and timed actions (daily and weekly schedulers, exception dates), recipes, security and user management, e-mail and RSS feeds.

- Wide selection of communication drivers available with multiple-driver communication capability.
- Remote monitoring and control with Client-Server functionality. Web interface based on HTML5
- Off-line and on-line simulation with JMobile Studio.
- Powerful scripting language for automating HMI applications. Efficient script debugger improves productivity in application development.
- Rich gallery of objects and symbols
- Mediaplayer widget
- IP Network camera widget
- Optional CODESYS integrated PLC.






Technical Data

Display Type Resolution Active display area Colors Backlight Brightness Dimming	TFT 800x480, WVGA 7" diagonal 64K White LED 400 Cd/m ² typ. Yes	Power supply voltage Current consumption Fuse Weight Battery Environmental Conditions	24 Vdc (10 to 32 Vdc) 0.9A at 24Vdc (max.) Automatic Approx 1.5 Kg Rechargeable Lithium battery, not user-replaceable
System Resources Operating System CPU Flash RAM	Microsoft Windows CE 6.0 ARM Cortex-A8 1GHz 256 MB 256 MB	Operating temperature Storage temperature Operating and storage humidity Protection class	-20 to +60 °C (vertical installation) -40 to +85 °C 5 – 85 % relative humidity, non-condensing IP69K (front)
Operator Interface Touchscreen	Projected Capacitive	Dimensions	IP20 (rear)
Interfaces Ethernet port USB port	2 10/100 Mbit with integrated Switch 2 Host interface v.2.0	Faceplate LxH Cutout AxB Depth D+T	215x175 mm (8.46x6.89") 176x136 mm (6.93x5.35") 46+9.5 mm (1.85+0.37")
Serial Port Expansion Slot Memory Card	RS-232, RS-485, RS-422, software configurable 2 Optional Plug-in SD Card Slot	Approvals CE	Emission EN 61000-6-4 Immunity EN 61000-6-2
Functionality Hardware Real Time Clock	Yes, with battery back-up		for installation in industrial environments
Buzzer	Yes, audible feedback for touchscreen	UL pending	cULus
Ratings			





Dimensions



Connections







Ordering Information

Model	Part Number	Description
eTOP507MFB	+ETOP507MU1F1	7" widescreen TFT color projected capacitive touchscreen.
		Stainless steel bezel. Ethernet and USB interfaces. JMobile
		runtime. White front panel.
eTOP507MFB	+ETOP507MU4F1	7" widescreen TFT color projected capacitive touchscreen.
		Stainless steel bezel. Ethernet and USB interfaces. JMobile
		runtime. Blue front panel.

ptn0524 Ver. 1.0

Copyright © 2015 Exor International S.p.A. - Verona, Italy

Subject to change without notice

The information contained in this document is provided for informational purposes only. While efforts were made to verify the accuracy of the information contained in this documentation, it is provided "as is" without warranty of any kind.

www.exorint.net