



The VLX-60 is a member of the VLX series of Electric Encoders[™] a product line based on Netzer Precision Motion Sensor proprietary technology. EE products are characterized by features that enable unparalleled performance:

- Low profile (<10 mm)
- Hollow shaft (Stator / Rotor)
- No bearings or other contact elements
- High resolution and unparalleled precision
- High tolerance to temperature extremes, shock, moisture, EMI, RFI and magnetic fields
- Very low weight
- Holistic signal generation
- Digital interfaces for absolute position

General

Angular resolution	18-20 bit	
Maximum tested static error	≤ 0.015°	
Extended accuracy static error	≤ 0.010°	
Maximum operational speed	4,000 rpm	
Measurement range	Single turn, unlimited	
Rotation direction	Adjustable CW/CCW*	
* Default same direction from bottom side of the encoder		

Mechanical

Allowable mounting eccentricity	±0.1 mm
Allowable rotor axial motion	±0.1 mm
Rotor inertia	1,930 gr · mm ²
Total weight	14
Outer Ø /Inner Ø/ Height	60 / 25/ 8 mm
Material (stator, rotor)	FR4
Nominal air gap (stator, rotor)	0.6 mm

Electrical

Supply voltage	5V ± 5%
Current consumption	90 mA
Interconnection	Connector

The holistic structure of the Electric EncoderTM makes it unique: Its output reading is the averaged outcome of the entire area of the rotor. This feature allows the EE a tolerant mechanical mounting and to deliver outstanding precision.

Due to the absence of components such as ball bearings, flexible couplers, glass discs, light sources and detectors along with very low power consumption enables the EE to deliver virtually failure-free performance in nearly all types of conditions.

The internally shielded, DC- operated EE includes an electric field generator, a field receiver, sinusoidal-shaped dielectric rotor, and processing electronics.

The EE output is a digital serial synchronous with absolute position single turn.


This combination of high precision, low profile and, low weight has made Netzer Precision encoders highly reliable and particularly well suited to a wide variety of industrial automation applications.


Environmental

EMC	IEC 6100-6-2, IEC 6100-6-4
Operating temperature	-25°C to +65°C
Storage temperature	-40°C to +100°C
Relative humidity	98% Non condensing
Shock endurance	100 g for 11 ms
Vibration endurance	20 g 10 – 2000 Hz
Protection	IP 40

Calibration / Compensation

Offsets	Automatic / Manual
Signals level	Automatic / Manual
Signals integrity	Error / Warning report
Thermal	Error / Warning report
Zero position	Manual





Sold & Serviced By:











Digital SSi Interface

Synchronous Serial Interface **(SSI)** is a point to point serial interface standard between a master (e.g. controller) and a slave (e.g. sensor) for digital data transmission.



	Description	Recommendations
n	Total number of data bits	12 - 22
Т	Clock period	
f= 1/T	Clock frequency	0.1 - 5.0 MHz
Tu	Bit update time	90 nsec
Тр	Pause time	26 - ∞ µsec
Tm	Monoflop time	>25 µsec
Tr	Time between 2 adjacent requests	Tr > n*T+26 µsec
fr=1/Tr	Data request frequency	



SSi / BiSS output signal parameters

Output code	Binary
Serial output	Differential RS-422
Clock	Differential RS-422
Clock Frequency	0.1 ÷ 5.0 MHz
Position update rate	35 kHz (Optional - up to 375 KHz)

SSi/BiSS interface pin/cable color code

DF-13 on-board connector pin#	DB9 F (cable end) pin#	Cable Color	Function
7	1	Blue	CLK - / NCP RX -
8	2	Gray	CLK + / NCP RX +
5	3	Green	DATA + / NCP TX +
6	4	Yellow	DATA - / NCP TX -
4	5	Black	GND
3	8	Red	5v

Software tools: (SSi / BiSS - C)

Advanced calibration and monitoring options are available by using the factory supplied <u>Electric Encoder Explorer software</u>. This facilitates proper mechanical mounting, offsets calibration and advanced signal monitoring.





Operational Mod

320.202

Digital BiSS-C Interface

BiSS – C Interface is unidirectional serial synchronous protocol for digital data transmission where the Encoder acts as "slave" transmits data according to "Master" clock. The BiSS protocol is designed in B mode and C mode (continuous mode). The BiSS-C interface as the SSi is based on RS-422 standards.



Bit #		Description	Default	Length
28	Ack	Period during which the encoder calculates the absolute position, one clock cycle	0	1/clock
27	Start	Encoder signal for "start" data transmit	1	1 bit
26	"O"	"start" bit follower	0	1 bit
825	AP	Absolute Position encoder data		
7	Error	Error (BIT Optional)	1	1 bit
6	Warn.	Warning (non active)	1	1 bit
05	CRC	The CRC polynomial for position, error and warning data is: $x6 + x1 + x0$. It is transmitted MSB first and inverted. The start bit and "0" bit are omitted from the CRC calculation.		6 bits
	Timeout	Elapse between the sequential "start"request cycle's.		25 µs

DATA SHEET





Ordering Code

		VLX - 60) - S H	- C H		
VLX Pr	oduct l	ine			Interco	onnection
					Н	Connector - Horizontal
Outer [Diamete	er			V	Connector - Vertical
Output	t					
S	SSi					
I	BiSS					
Resolu	ition					
Code	Bit	CPR				
G	18	262,144				
Н	19 ¹	524,288				


Optional Accessories

Accessories - cables, optional

SSi / BiSS	Remarks	
CB-00088-250	AWG30, 250 mm	
CB-00088-500	AWG30, 500 mm	



Netzer Cat No.: CB 00014 Provider: Ray-Q USA. CAT No.: RQ 213210 Cable: 30 AWG twisted pair (3): 2 (30 AWG 25/44 tinned copper, Insulation: PFE Ø 0.15 to Ø 0.6 \pm 0.05 OD). Temperature rating: -60 to +150 Deg C. Braided shield: Thinned copper braided 95% min. coverage. Jacket: 0.44 silicon rubber (NFA 11-A1) Ø3.45 ±0.2 OD



Related documents

LX-60 User Manual: Mechanical, Electrical and calibration setup.

Demonstration Kit

DKIT-VLX-60-SG with SSi interface

DKIT-VLX-60-IG withe BiSS interface Includes, mounted encoder on rotary jig, and RS-422 to USB converter.

Sold & Serviced By:

ELECTROMATE 877-737-8698 sales@electromate.com www.electromate.com



Notes

20

1 Resolution - optional, call

1,048,576

E



7.51

\connector's max. height/

0.<u>60 ±0.10 air gap</u> 1.60

3.89-

2.20-

0



2.23 ±0.10

// 0.05 B


□ 0.05

В

for rotor clearance fit 7 0.05 Ø25 min. SECTION B-B equals to rotor min. ϕ \emptyset 33 max. 0.05 B () 0.1 A Rotor's OD and ID Ø52.50 Ø25 otin 29pitch circle otin for. 0 rotor mounting **[**]° 0.1 A 6 18 Ann Ĵ<u>ē</u>ć. "....... 0 C 6

SECTION A-A

 ϕ 53 min.



Unless otherwise specified Dimensions are in: mm Surface finish: N6 Linear tolerances: ±0.1 deg DATA SHEET